
Tetragono Floor 90 - 3000K

Ernesto Gismondi



IP65 **≜**



LUMINAIRE

- Watt: **15W**

- Voltage: **220V-240V**

- Delivered lumen output: 481lm

- CCT: **3000K** - Efficiency: **34%**

- Efficacy: **32.07lm/W**

- CRI: 90

DESCRIPTION

Consists of lamp and supporting pole. Lamp support in extruded EN-AW-6060 aluminium, subjected to chromate treatment and painted, height 900mm, with painted steel base flange, with holes for floor installation by means of log bolts or dowels. Lighting unit in die-cast EN-AB 47100 aluminium painted with 3-stage outdoor treatment: nanotechnologies, anti-oxidizing primer, polyester paint. Provided with metalized polycarbonate reflectors. UV resistant diffuser in shock resistant polycarbonate with bright finish. AISI 316 fixing screws and silicone gaskets. Provided with cable and IP67 connector for the connection to the mains suitable for 5-13.5mm diameter cables. IP Rating IP65. Insulation class I. Technical features in compliance with EN60598-1.

FEATURES

Product Code: **T417200W00**Colour: **Grey antracite**

- Installation: Floor

- Material: **Aluminum, polycarbonate**

Series: Architectural Outdoordesign by: Ernesto Gismondi

DIMENSIONS

Length: 130 mmWidth: 130 mmHeight: 900 mm

Impact Resistance: **IK10**Glow Wire Test: **650°**

