
La linea - 2,5mt

BIG - Bjarke Ingels Group



IP65 **(★ (★** Dimmerable: **+0**-



LUMINAIRE

- Watt: 15W/m

- Delivered lumen output: 960 lm/m

CCT: 3000KEfficiency: 100%Efficacy: 64lm/W

- CRI: 95

- Dimmable Typology: APP, Push, Dali

Notes

5 wall/ceiling supports included Weight 1,4 kg/m Driver not included

DESCRIPTION

La Linea is a flexible tube of light capable to freely twist and turn in space according to undefined geometries. It easily fits into indoor and outdoor spaces with fixing elements that disappear into the cross section, allowing countless applications in a broad variety of locations thanks to an unprecedented combination of factors including light quality, IP protection grade and flexibility. Available in 2.5 and 5-meter lengths.

La Linea 25 increasingly becomes a communicative as well as a functional tool, adding values and meanings to its light through the expressiveness of its graphic sign. It has excellent light performance in terms of quantity and

It has excellent light performance in terms of quantity and quality, allowing not only the characterisation of a space but also its correct lighting.

The slim section with lengths of 5, 10 and 20 meters can be overlapped to create weaving and leaving the freedom to follow complex geometries like figures created by a single line. It combines innovation with emotion, liaising with manbuilt and natural spaces in which it is applied. It is sustainable, reconfigurable and long-lasting.

FEATURES

- Product Code: **T4601010**

- Colour: White

- Installation: Ceiling, Wall

 Material: High diffusion optical silicone lamp body. Transparent technopolymer wall mounts.
Steel recessed ceiling mounts, steel and aluminum surface-mounted ceiling mounts.

- Series: Design Collection, Architectural Outdoor

- design by: BIG - Bjarke Ingels Group

DIMENSIONS

Length: 2500 mmDiameter: 40 mm



Accessories

NO IMAGE AVAILABLE	Additional wall/ceiling support R304975	NO IMAGE AVAILABLE	Driver 90W - CV 100-240VAC - 24VDC - 0-10V - 250x63x30mm (LxWxH) - IP65 DV1075
NO IMAGE AVAILABLE	Driver 90W - CV 110-240VAC - 24VDC - Push & APP - 250x100x52mm (LxWxH) - IP20 DV1075APP	NO IMAGE AVAILABLE	Driver 90W - CV 100-240VAC - 24VDC - DALI/On-Off - 250x63x30mm (LxWxH) - IP65 DV1076
no image available	Powerkit 96W - CV 110-240VAC - 24VDC - On-Off - 400x110x52mm (LxWxH) - IP20 A4681210	no IMage Available	Powerkit 96W - CV 110-240VAC - 24VDC - DALI/0- 10/Push - 400x110x52mm (LxWxH) - IP20 A4681010
NO IMAGE AVAILABLE	Powerkit 96W - CV 110-240VAC - 24VDC - Push & APP - 400x110x52mm (LxWxH) - IP20 A4681010APP	NO IMAGE AVAILABLE	Powerkit 96W - CV 110-240VAC - 24VDC - Push & APP - 400x104x61mm (LxWxH) - IP65 T4681010APP

