

ZIRKOL LINEAR UGR CEILING

New lamp of the collection, Zirkol Linear UGR is equipped with a particular optical unit that allows direct emission with a reduced glare index (UGR <19). Aluminium structure available in black or white finish and two LED colour temperatures: 3000K or 4000K. Now Zirkol Linear UGR lamp is presented in the new Ceiling version with driver on-board. It is particularly suitable for installation in offices and work environments where high visual comfort is required.



1,4M CEILING | 3000K

LAMPING

Source	linear LED
Total power	40W
Emission	direct UGR < 19
Switching	ON/OFF
Tension	220/240V
Color temperature	3000K
Luminous flux	3600lm
Typ CRI	>90
IP class	20
Dimensions	140x2,6x5
Materials	aluminium
Notes	1 x driver Ultralim included, ceiling attachments included RAL 9005 black RAL 9016 white
Customization options	lengths
Net lamp weight	3,2 kg

Codes

BZRLU414I42WBO

BZRLU414I42WNE

Structure

white


black

PACKAGE

Package 01

Dimension: 204x11x11 cm / Gross weight: 5 kg

Certificazioni



1,4M CEILING | 4000K

LAMPING

Source	linear LED
Total power	40W
Emission	direct UGR < 19
Switching	ON/OFF
Tension	220/240V
Color temperature	4000K
Luminous flux	3700lm
Typ CRI	>90
IP class	20
Dimensions	140x2,6x5
Materials	aluminium
Notes	1 x driver Ultraslim included, ceiling attachments included RAL 9005 black RAL 9016 white
Customization options	lengths
Net lamp weight	3,2 kg

Codes

BZRLU414I42NBO

BZRLU414I42NNE

Structure

white

black

PACKAGE

Package 01

Dimension: 204x11x11 cm / Gross weight: 5 kg

Certificazioni

