


Adamas

220-240V AC dimmable (Push DIM)
C18106.023.0527




Data sheet

CODE	C18106.023.0527
SYSTEM POWER CONSUMPTION	9W
EFFICACY	69.33lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L70 (B50) 60.000h
COLOUR TEMPERATURE	2700K Ra>90
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
ELECTRICAL CONFIGURATION	dimmable (Push DIM)
DRIVER	integrated included
NOMINAL LUMINOUS FLUX	1344lm
LUMEN OUTPUT	624lm
EFFICIENCY	46.4%
WEIGHT	4,80 Kg
PROTECTION DEGREE	IP20
COLOUR TOLLERANCES	SDCM 3
PACKING DIMENSIONS	0,0 x 0,0 x 0,0 cm



Table lighting fixture for interiors, with direct light emission.
Aluminium frame with polyacrylic paint finish in mat black or mat brass.
Diffuser screen in acrylic material with satin finish.
Handmade and hand-ground blown glass in bronze colour.
Steel closing plate with polyacrylic paint finish.
Metal base with polyacrylic paint in mat black or mat brass finish, with integrated dimmer button.
Supplied complete with black fabric power cable and plug adapter.

Technical drawing



Polar diagram