

m o o o i

Prop Light Suspended

BERTJAN POT



"We have round lights, we have straight lights. We have them with lights on one side, we have them with lights on two sides. You can hang them high, low, horizontally, vertically or even hang them in an angle. Put them on the floor, hang them on your wall or down from the ceiling. We find it very hard to imagine an interior where this prop is not in place" - Bertjan Pot

Detailing



A theatrical, extravagant look that is suitable for spaces with both low and high ceilings.

Colours

2700K
Soft White


Prop Light Suspended / Double

Dimensions

98cm | 38.6"



18cm | 7.1"



17cm | 6.7"

Product

WIDTH 98cm | 38.6"

HEIGHT 18cm | 7.1"

DEPTH 18cm | 7.1"

WEIGHT NETTO 6kg | 13.23lbs

Packaging

WIDTH 30cm | 11.8"

HEIGHT 30cm | 11.8"

CUBAGE 0.12m³ | 4.23ft³

LENGTH 133cm | 52.4"

WEIGHT 10kg | 22.05lbs

Technical CE

MATERIAL

HIPS housing, PMMA light guide, glass bulbs.

ENERGY LABEL

A

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

36

INPUT VOLTAGE

110-240V

MAX POWER CONSUMPTION

21W

LIFETIME

50000 hours

CABLE LENGTH

400cm | 157.5"

COLOUR TEMPERATURE

2700 K (max)

LIGHT DIRECTION

All directions

DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

SHAPE

Linear

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

CABLE COLOUR

Transparent with tinned cores

CANOPY

Pebble II White, ABS

CRI

80

LIGHT OUTPUT

1600 lm

See last page for more information about the dimming possibilities.



Technical UL

MATERIAL

HIPS housing, PMMA light guide, glass bulbs.

ENERGY LABEL

A

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

36

INPUT VOLTAGE

110-240V

MAX POWER CONSUMPTION

21W

LIFETIME

50000 hours

CABLE LENGTH

400cm | 157.5"

COLOUR TEMPERATURE

2700 K (max)

LIGHT DIRECTION

All directions

DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

SHAPE

Linear

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

CABLE COLOUR

Transparent with tinned cores

CANOPY

Pebble II White, ABS

CRI

80

LIGHT OUTPUT

1600 lm

See last page for more information about the dimming possibilities.



Prop Light Suspended / Double Horizontal

Dimensions

98cm | 38.6"



17cm | 6.7"



18cm | 7.1"

Product

WIDTH 98cm | 38.6"

HEIGHT 18cm | 7.1"

DEPTH 17cm | 6.7"

WEIGHT NETTO 6kg | 13.23lbs

Packaging

WIDTH 30cm | 11.8"

HEIGHT 30cm | 11.8"

CUBAGE 0.12m³ | 4.23ft³

LENGTH 133cm | 52.4"

WEIGHT 10kg | 22.05lbs

Technical CE

MATERIAL

HIPS housing, PMMA light guide, glass bulbs.

ENERGY LABEL

A

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

36

INPUT VOLTAGE

110-240V

MAX POWER CONSUMPTION

21W

LIFETIME

50000 hours

CABLE LENGTH

400cm | 157.5"

COLOUR TEMPERATURE

2700 K (max)

LIGHT DIRECTION

All directions

DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

SHAPE

Linear

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

CABLE COLOUR

Transparent with tinned cores

CANOPY

Pebble II White, ABS

CRI

80

LIGHT OUTPUT

1600 lm

See last page for more information about the dimming possibilities.



Technical UL

MATERIAL

HIPS housing, PMMA light guide, glass bulbs.

ENERGY LABEL

A

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

36

INPUT VOLTAGE

110-240V

MAX POWER CONSUMPTION

21W

LIFETIME

50000 hours

CABLE LENGTH

400cm | 157.5"

COLOUR TEMPERATURE

2700 K (max)

LIGHT DIRECTION

All directions

DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

SHAPE

Linear

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

CABLE COLOUR

Transparent with tinned cores

CANOPY

Pebble II White, ABS

CRI

80

LIGHT OUTPUT

1600 lm



See last page for more information about the dimming possibilities.



Prop Light Suspended / Round Double

Dimensions

73cm | 28.7"



Product

WIDTH 73cm | 28.7"
HEIGHT 25cm | 9.8"
DEPTH 73cm | 28.7"
DIAMETER 73cm | 28.7"
WEIGHT NETTO 9kg | 19.84lbs

Packaging

WIDTH 88cm | 34.6"
HEIGHT 34cm | 13.4"
CUBAGE 0.27m³ | 9.4ft³
LENGTH 89cm | 35"
WEIGHT 15kg | 33.07lbs

Technical CE

MATERIAL

HIPS housing, PMMA light guide, glass bulbs.

ENERGY LABEL

B

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

96

INPUT VOLTAGE

110-240V

MAX POWER CONSUMPTION

41W

LIFETIME

50000 hours

CABLE LENGTH

400cm | 157.5"

COLOUR TEMPERATURE

2700 K (max)

LIGHT DIRECTION

All directions

DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

SHAPE

Disc

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

CABLE COLOUR

Transparent with tinned cores

CANOPY

Pebble II White, ABS

CRI

80

LIGHT OUTPUT

1936 lm

See last page for more information about the dimming possibilities.



Technical UL

MATERIAL

HIPS housing, PMMA light guide, glass bulbs.

ENERGY LABEL

B

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

96

INPUT VOLTAGE

110-240V

MAX POWER CONSUMPTION

41W

LIFETIME

50000 hours

CABLE LENGTH

400cm | 157.5"

COLOUR TEMPERATURE

2700 K (max)

LIGHT DIRECTION

All directions

DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

SHAPE

Disc

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

CABLE COLOUR

Transparent with tinned cores

CANOPY

Pebble II White, ABS

CRI

80

LIGHT OUTPUT

1936 lm



See last page for more information about the dimming possibilities.



Prop Light Suspended / Round Single

Dimensions

73cm | 28.7"



Product

WIDTH 73cm | 28.7"
HEIGHT 19cm | 7.5"
DEPTH 73cm | 28.7"
DIAMETER 73cm | 28.7"
WEIGHT NETTO 7kg | 15.43lbs

Packaging

WIDTH 88cm | 34.6"
HEIGHT 34cm | 13.4"
CUBAGE 0.27m³ | 9.4ft³
LENGTH 89cm | 35"
WEIGHT 15kg | 33.07lbs

Technical CE

MATERIAL

HIPS housing, PMMA light guide, glass bulbs.

ENERGY LABEL

B

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

48

INPUT VOLTAGE

110-240V

MAX POWER CONSUMPTION

21W

LIFETIME

50000 hours

CABLE LENGTH

400cm | 157.5"

COLOUR TEMPERATURE

2700 K (max)

LIGHT DIRECTION

All directions

DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

SHAPE

Disc

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

CABLE COLOUR

Transparent with tinned cores

CANOPY

Pebble II White, ABS

CRI

80

LIGHT OUTPUT

1078 lm

See last page for more information about the dimming possibilities.



Technical UL

MATERIAL

HIPS housing, PMMA light guide, glass bulbs.

ENERGY LABEL

B

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

48

INPUT VOLTAGE

110-240V

MAX POWER CONSUMPTION

21W

LIFETIME

50000 hours

CABLE LENGTH

400cm | 157.5"

COLOUR TEMPERATURE

2700 K (max)

LIGHT DIRECTION

All directions

DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

SHAPE

Disc

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

CABLE COLOUR

Transparent with tinned cores

CANOPY

Pebble II White, ABS

CRI

80

LIGHT OUTPUT

1085 lm

See last page for more information about the dimming possibilities.




Prop Light Suspended / Single

Dimensions

98cm | 38.6"



18cm | 7.1"



13cm | 5.1"

Product

WIDTH 98cm | 38.6"

HEIGHT 13cm | 5.1"

DEPTH 18cm | 7.1"

WEIGHT NETTO 5kg | 11.02lbs

Packaging

WIDTH 30cm | 11.8"

HEIGHT 30cm | 11.8"

CUBAGE 0.12m³ | 4.23ft³

LENGTH 133cm | 52.4"

WEIGHT 10kg | 22.05lbs

Technical CE

MATERIAL

HIPS housing, PMMA light guide, glass bulbs.

ENERGY LABEL

A

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

18

INPUT VOLTAGE

110-240V

MAX POWER CONSUMPTION

21W

LIFETIME

50000 hours

CABLE LENGTH

400cm | 157.5"

COLOUR TEMPERATURE

2700 K (max)

LIGHT DIRECTION

All directions

DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

SHAPE

Linear

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

CABLE COLOUR

Transparent with tinned cores

CANOPY

Pebble II White, ABS

CRI

80

LIGHT OUTPUT

499 lm

See last page for more information about the dimming possibilities.



Technical UL

MATERIAL

HIPS housing, PMMA light guide, glass bulbs.

ENERGY LABEL

A

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

18

INPUT VOLTAGE

110-240V

MAX POWER CONSUMPTION

21W

LIFETIME

50000 hours

CABLE LENGTH

400cm | 157.5"

COLOUR TEMPERATURE

2700 K (max)

LIGHT DIRECTION

All directions

DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

SHAPE

Linear

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

CABLE COLOUR

Transparent with tinned cores

CANOPY

Pebble II White, ABS

CRI

80

LIGHT OUTPUT

499 lm

See last page for more information about the dimming possibilities.



Dimming & Lighting Control

Mains, Trailing edge, Reverse phase

Control the mood with ease. This light fixture can be dimmed using an external Electronic Low Voltage dimmer. Simply connect it to an existing outlet—no need to rewire your home. Choose a dimmer designed for LED lights, suitable for 5 watts or lower, and supporting a C-type (capacitive load). This ensures compatibility and smooth operation. As with all delicate lighting, the experience of dimming may occasionally bring a flicker, hum, or soft buzz.

Compatible models: Double CE, Double UL, Double Horizontal CE, Double Horizontal UL, Double Vertical CE, Double Vertical UL, Round Double CE, Round Double UL, Round Double Vertical CE, Round Double Vertical UL, Round Single CE, Round Single UL, Single CE, Single UL
